

MaxiCharger DC Compact

50kW



MaxiCharger DC Compact

Big power and big value in a compact package



Fast and Effective

Built to increase charging efficiency

- Dual-ports provide up to 50kW of power
- Charge 2 vehicles simultaneously
- A 30 min charge equates to 138 km of range



Compact Design

Optimized for any location

- Ultra-compact with big DC power in a small package
- Flexible installation allows for fixed or mobile positioning
- DC Compact has low installation costs, meaning a faster ROI due to reduced capital expenditures for the site operator



Smart Advertising and Communication Platform

Improve your ROI

- User-friendly 21.5-inch LCD touch screen
- Powered by smart operating system, Android 10 with enhanced advertising placements
- Communicate, promote or attract customers generating new revenue streams

A Closer Look at the MaxiCharger DC Compact



OCPP Compliance



18 Safety Monitoring Items



Compatible with CCS2, CHAdeMO



One Stop Cloud Network Management



Plug & Charge



APP, RFID Card, Credit Card, Mobile Payment




96% Charging Efficiency



Smart Charging



Weather Resistant



Technical Specifications

DC Output Connection

Charging mode	Mode 4: CCS2
Output power	Rated power 50kW
Output voltage	150 - 950V
Max output current	CCS2: 133A
Number of outputs	2*CCS2
Peak efficiency	96%

AC Input Connection

Earthing system	3P, N, PE
Input voltage	3-phase 400V AC±10%
Input frequency	50/60 Hz
Power factor	≥0.99
Harmonic distortion (THDi)	≤5%

General Characteristics

IP and IK rating	IP54; IK10
Operating altitude	2000m
Operating temperature range	-30°C ~ +50°C
Storage temperature range	-40°C ~ +70°C
Mounting	Pedestal, wall mounting or wheels
Dimensions (H×W×D)	1000 × 550 × 265 mm
Screen type	21.5 inch LCD touch screen (1920*1080)
Cable length	5.5m standard; 7.5m optional

User Interface

Status indication	LED / LCD / APP
User interface	Autel Charge APP; Autel Charge Cloud
Connectivity	4G, Wi-Fi, Ethernet
Communication protocols	OCPP 1.6J (Can be upgraded to OCPP 2.0.1 later)
User authentication	APP, RFID card

Software Update

OTA updates via web portal

Certification and Standards

Safety and compliance	IEC 61851-1; IEC 61851-23; IEC 61851-21-2; ISO 15118
EMC compliance	CE, EMC Class A
Warranty	24 months, warranty extension possible

* All pictures shown are for illustration purpose only, actual product and specifications may vary due to product enhancement

AUTEL[®]

Autel Europe GmbH

☎ Phone: +49(0)89 540299608

✉ E-mail: evinfo.eu@autel.com

🌐 Website: autelenergy.com

Autel Energy

